



TRANSFORMADORES DE PROTECCIÓN (ENCAPSULADOS EN RESINA)




MODELO	PRIMARIO PASANTE							
	TPR60		TPR80		TPR100		TPR125	
Barra	-		-		-		-	
Cable	Ø60		Ø80		Ø100		Ø125	
Precisión	5P10	5P20	5P10	5P20	5P10	5P20	5P10	5P20
I _{pn} (A)	VA		VA		VA		VA	
100	10	5						
150	15	7						
200	20	10						
250	25	12	12	5				
300	30	15	15	7				
400	40	20	22	10				
500	50	25	30	12	15	7		
600	60	30	35	15	15	8		
750	75	38	45	18	20	10		
800	80	40	48	20	25	12		
1000	100	50	48	20	30	15	20	10
1200			48	22	30	17	30	15
1500			73	28	40	20	30	15
2000			97	35	60	30	30	15
2500					65	35	40	20
3000					65	35	40	20
4000					80	45	50	25
5000					120	70	70	35

DIMENSIONES



MODELOS	A	B
TPR60	124	120
TPR80	136	100
TPR100	150	100
TPR125	166	100

Dimensiones en mm.



MODELOS	A	B	C	D	E	F	G
TPR60	62	211	80	185	124	110	93
TPR80	82	231	60	205	136	120	103
TPR100	102	251	60	225	150	130	113
TPR125	127	276	60	250	166	143	125

Dimensiones en mm.